



Rotor-stator Homogenizers

High shear laboratory homogenizers are designed to process tough samples quickly and efficiently without compromising the sample. Faster processing times mean less chance of heat degradation to the sample. These motors are available in hand-held or stand-mounted configurations with speeds of up to 35,000 rpm. Homogenizers are a standard piece of equipment for any lab. Not sure which configuration will work best for your application? Contact our technical support team at 1-800-776-4431.







ROTOR-STATOR HOMOGENIZERS

Economical Homogenizer ///

OMNI TISSUE MASTER — Economical Homogenizing Solution

Economically priced **Omni Tissue Masters** are well suited for customers who are homogenizing with little variation in sample size. Omni Tissue Masters include a stainless steel generator probe making it is a great choice for a laboratory with many applications but a limited budget. *Please note: Omni Tip™ Disposable Probes are not compatible with Tissue Master homogenizers.*



PRODUCT FEATURES: CE

- Includes choice of 5 mm, 7 mm or 10 mm stainless steel rotor stator probe
- Variable motor speed control from 5,000 to 35,000 rpm
- Most samples processed in under one minute
- Easy to disassemble and clean
- Portable and lightweight
- Hand-held or stand mountable
- Quiet operation, under 72 db
- Processing Range: 0.20 mL to 100 mL
- 1-year motor warranty

Tissue Master 125 Watt Homogenizer

Ideal for soft tissue applications and emulsions
Includes 125 watt motor, stainless steel generator probe & instruction manual

Description	Processing Range	Order #
115V Omni Tissue Master 125 with 5 mm Probe	0.20 mL - 5 mL	TM125-115-05
115V Omni Tissue Master 125 with 7 mm Probe	0.25 mL - 30 mL	TM125-115
115V Omni Tissue Master 125 with 10 mm Probe	1.5 mL - 100 mL	TM125-115-10
220V Omni Tissue Master 125 with 5 mm Probe	0.20 mL - 5 mL	TM125-220-05
220V Omni Tissue Master 125 with 7 mm Probe	0.25 mL - 30 mL	TM125-220
220V Omni Tissue Master 125 with 10 mm Probe	1.5 mL - 100 mL	TM125-220-10
Motor Stand Assembly - includes baseplate, post & three prong clamp		F22000

Tissue Master 125 Watt Homogenizer Package

Includes the Tissue Master 125 homogenizer motor and three stainless steel generator probes (5 mm, 7 mm & 10 mm)

Description	Processing Range	Order #
115V Omni Tissue Master 125 Homogenizer Package	0.20 mL - 100 mL	TMP125-115
220V Omni Tissue Master 125 Homogenizer Package	0.20 mL - 100 mL	TMP125-220

Tissue Master Generator Probes

Description	Processing Range	Order #
5 mm Tissue Master Probe	0.20 mL - 5 mL	F2107-05
7 mm Tissue Master Probe	0.25 mL - 30 mL	F2107
10 mm Tissue Master Probe	1.5 mL - 100 mL	F2107-10



Shown with optional stand assy (F22000)



Hand-held or Post-Mountable Homogenizer ///

OMNI TH — Tissue Homogenizer

The **Omni TH** is a powerful tissue homogenizer that was designed to handle a wide range of samples from 0.20 mL to 100 mL. The TH can usually process a tissue sample in less than 30 seconds. It is compatible with a wide variety of stainless steel generator probes for flexibility in application requirements. Patented Omni Tip™ Disposable Generator Probes, in both soft tissue and hard tissue versions, are available for customers concerned with cross-contamination. Stainless steel generator probes are recommended for larger and tougher sample types.

The Omni TH will accommodate a wide range of applications such as tissue homogenization, emulsions and suspensions, cell disruption, protein extraction and medical research. It is lightweight enough to be hand-held and can also be mounted to a motor stand for convenience.



PRODUCT FEATURES: CE

- Powerful 125 watt motor
- Lightweight ergonomic design
- Quiet operation, under 72db
- ¼ turn bayonet probe mounting system for fast release
- Variable speed control from 5,000 to 35,000 rpm with separate power switch to maintain last speed setting
- Available in convenient Omni Tip Homogenizing Kits
- 1-year motor warranty
- Processing Range: 0.20 mL to 100 mL

Omni TH Tissue Homogenizer

Includes TH motor, tool kit, motor clamp for stand mounting and instruction manual.

Omni Tips™ and Stainless Steel Generator Probes sold separately

Description	Processing Range	Order #
115V Omni TH: Tissue Homogenizer (motor only)	0.20 mL - 100 mL	TH115
220V Omni TH: Tissue Homogenizer (motor only)	0.20 mL - 100 mL	TH220

Omni TH Homogenizer Package

Includes TH Motor, 3 stainless steel generator probes (5 x 75 mm flat bottom, 7 x 95 mm saw tooth, 10 x 95 mm saw tooth) and motor clamp stand assembly

Description	Order #
115V Omni TH Homogenizer Package	THP115
115V Omni TH & Motor Stand Assembly (no probes)	TH115-K
220V Omni TH Homogenizer Package	THP220
220V Omni TH & Motor Stand Assembly (no probes)	TH220-K
Stand Assembly includes baseplate and rod	S1000



Shown with optional Stand Assembly (Order #S1000)



ROTOR-STATOR HOMOGENIZERS

Stainless Steel Generator Probes ///

Compatible with Omni TH Homogenizer

Stainless Steel Generator Probes are ideal for larger sample volume, larger initial sample size, and tougher tissue types. They are also resistant to most organic solvents commonly used during homogenization.



Stainless Steel Generator Probes

Diameter	Processing Range	Recommended Vessel Size	Length	Type	Resulting Particle Size	Order #
5 mm	0.20 mL - 5 mL	Vessel with a minimum inner diameter of 6 mm	75 mm	Flat bottom	Fine	G5-75
			75 mm	Flat bottom - Wide Window	Coarse	G5-75W
			95 mm	Flat bottom	Fine	G7-95
			95 mm	Flat bottom - Wide Window	Coarse	G7-95W
7 mm	0.25 mL - 30 mL	Vessel with a minimum inner diameter of 8 mm	95 mm	Saw Tooth	Fine	G7-95ST
			95 mm	Saw Tooth - Wide Window	Coarse	G7-95STW
			195 mm	Flat bottom	Fine	G7-195
			195 mm	Flat bottom - Wide Window	Coarse	G7-195W
			195 mm	Saw Tooth	Fine	G7-195ST
			195 mm	Saw Tooth - Wide Window	Coarse	G7-195STW
10 mm	1.5 mL - 100 mL	Vessel with a minimum inner diameter of 12.5 mm	95 mm	Saw Tooth	Fine	G10-95
			95 mm	Saw Tooth - Wide Window	Coarse	G10-95W
			195 mm	Saw Tooth	Fine	G10-195
			195 mm	Saw Tooth - Wide Window	Coarse	G10-195W

Stainless Steel Homogenizer Probe Disassembly Tool Kit

For use with generator probes listed above

Description	Order #
Stainless Steel Generator Probe Disassembly Tool Kit	T1001



Omni Tip™ Homogenizing Kits /// Everything you need to homogenize

Omni Tip™ Homogenizing Kits include everything you need to homogenize. These kits can be used to process samples with a range of 0.20 mL to 100 mL. They come complete with an Omni TH motor, Omni Tip™ adapter, 12 hard or soft tissue patented Omni Tip™ Disposable Generator Probes (7 mm x 110 mm), tool kit and a convenient storage case. The perfect solution for a small laboratory, this kit is cost effective and will process a wide range of applications for multiple users.

PRODUCT FEATURES:

- Ideal for applications requiring no cross-contamination, such as RNA, DNA extractions and PCR
- Variable speed controller from 5,000 to 35,000 rpm
- Omni Tips™ are economical and can be disposed of after use or autoclaved up to 7 times
- Kits are also available with stainless steel generator probes for more fibrous/tough samples
- Processing Range with Omni Tips: 0.25 mL - 30 mL
- Processing Range with stainless steel probes: 0.20 mL - 100 mL



Omni Tip Kit

Each Kit includes Omni Tissue Homogenizer, Omni Tip Adapter, 12 Soft Tissue and Hard Tissue Omni Tips™ (7 mm x 110 mm), storage case, motor mount, tool kit and manual.

Description	Order #
115V Omni Tip Kit with 6 Soft & 6 Hard Tissue Tips	TH115-PCR
220V Omni Tip Kit with 6 Soft & 6 Hard Tissue Tips	TH220-PCR

Soft Tissue Omni Tip Kit with 12 Omni Tip™ Probes For processing liquids, soft tissues, and samples that require gentle processing

Description	Order #
115V Soft Tissue Omni Tip™ Kit	TH115-PCRD
115V Soft Tissue Omni Tip™ Kit with 5 x 75 mm Stainless Steel Generator Probe (G5-75)	TH115-PCR5D
115V Soft Tissue Omni Tip™ Kit with 7 x 95 mm Stainless Steel Generator Probe (G7-95)	TH115-PCR7D
115V Soft Tissue Omni Tip™ Kit with 10 x 95 mm Stainless Steel Generator Probe (G10-95)	TH115-PCR10D
220V Soft Tissue Omni Tip™ Kit	TH220-PCRD
220V Soft Tissue Omni Tip™ Kit with 5 x 75 mm Stainless Steel Generator Probe (G5-75)	TH220-PCR5D
220V Soft Tissue Omni Tip™ Kit with 7 x 95 mm Stainless Steel Generator Probe (G7-95)	TH220-PCR7D
220V Soft Tissue Omni Tip™ Kit with 10 x 95 mm Stainless Steel Generator Probe (G10-95)	TH220-PCR10D



Hard Tissue Omni Tip Kit with 12 Omni Tip™ Probes For processing hard or frozen tissue samples

Description	Order #
115V Hard Tissue Omni Tip™ Kit	TH115-PCRH
115V Hard Tissue Omni Tip™ Kit with 5 x 75 mm Stainless Steel Generator Probe (G5-75)	TH115-PCR5H
115V Hard Tissue Omni Tip™ Kit with 7 x 95 mm Stainless Steel Generator Probe (G7-95ST)	TH115-PCR7H
115V Hard Tissue Omni Tip™ Kit with 10 x 95 mm Stainless Steel Generator Probe (G10-95)	TH115-PCR10H
220V Hard Tissue Omni Tip™ Kit	TH220-PCRH
220V Hard Tissue Omni Tip™ Kit with 5 x 75 mm Stainless Steel Generator Probe (G5-75)	TH220-PCR5H
220V Hard Tissue Omni Tip™ Kit with 7 x 95 mm Stainless Steel Generator Probe (G7-95ST)	TH220-PCR7H
220V Hard Tissue Omni Tip™ Kit with 10 x 95 mm Stainless Steel Generator Probe (G10-95)	TH220-PCR10H





ROTOR-STATOR HOMOGENIZERS

Hand-held or Post-Mountable Homogenizer ///

OMNI MICRO HOMOGENIZER — Battery-powered Tissue Homogenizer

The **Omni Micro Homogenizer** is a hand-held battery powered rotor-stator homogenizer designed for use inside or outside of a laboratory setting. The Micro Homogenizer is powered by 12 volt lithium ion battery that provides operating speeds from 5,000 to 30,000 rpm for rapid homogenization of samples in volumes from 0.20 mL to 100 mL. It is an ideal solution for field based homogenization procedures involving the processing of tissues or soft plant material. Compatible with stainless steel generator probes from 5 mm to 10 mm or disposable 7 mm Omni Tip™ disposable generator probes for customers concerned with cross contamination. Hybrid generator probes are also available for applications requiring the durability of stainless steel with the convenience and cleanliness of disposable probes.



PRODUCT FEATURES: CE

- Battery-driven cordless 35 watt motor
- Variable speed from 5,000 to 30,000 rpm
- Light weight portable homogenizer
- ¼ turn bayonet probe mounting for fast release
- Compatible with Omni Tip™ disposable probes, hybrid probes and stainless steel generator probes
- 1-year motor warranty

Omni Micro Homogenizer

Includes Micro Homogenizer motor, 12 volt battery, charging station, tool kit and instruction manual. *Omni Tips™ and Stainless Steel Generator Probes sold separately*

Description	Order #
115V Omni Micro Homogenizer (motor only)	UHB-115
220V Omni Micro Homogenizer (motor only)	UHB-220

Stainless Steel Generator Probes



Stainless Steel Generator Probes are ideal for larger sample volume, larger initial sample tissue size, and tougher tissue types. Stainless Steel Probes are also resistant to most organic solvents commonly used during homogenization. *Compatible with Micro Homogenizer, TH_Q, Prep 96, LH 96 and Omni Prep Homogenizers.*

Description	Processing Range	Order #
5 mm x 75 mm Stainless Steel Probe	0.2 mL - 5 mL	B5-075
5 mm x 75 mm Stainless Steel Probes (6 pack)	0.2 mL - 5 mL	B5-075-6
7 mm x 110 mm Stainless Steel Probe	0.25 mL - 30 mL	B7-110ST
7 mm x 110 mm Stainless Steel Probe (6 pack)	0.25 mL - 30 mL	B7-110ST-6
10 mm x 110 mm Stainless Steel Probe	1.5 mL - 100 mL	B10-110ST
10 mm x 110 mm Stainless Steel Probe (6 pack)	1.5 mL - 100 mL	B10-110ST-6
12 mm x 110 mm Stainless Steel Probe	1.5 mL - 125 mL	B12-110ST
12 mm x 110 mm Stainless Steel Probe (6 pack)	1.5 mL - 125 mL	B12-110ST-6



Hand-held or Post-Mountable Homogenizer ///

OMNI TH_Q — Digital Hand-held Tissue Homogenizer

The **Omni TH_Q** is a digital homogenizer that can handle a wide range of samples from 0.20 mL to 120 mL.

It provides reliable, repeatable performance with an **ultra-quiet brushless motor**. An integrated digital speed control stores the last set speed for ultimate repeatability.

The Omni TH_Q is compatible with Omni Tip™ disposable generator probes, stainless steel generator probes from 5 mm to 12 mm diameter and hybrid steel/plastic Omni Tips.

The Omni TH_Q is an ideal fit for a wide range of applications from tissue homogenization and dissociation, PD/PK studies, tablet disruption, emulsions and suspensions, cell disruption, food samples, and much more.

PRODUCT FEATURES: CE

- Three digit speed readout accurate to +/- <5% at top speed
- Integrated probe feedback to maintain consistent speed
- Whisper Drive Technology™ provides ultra quiet operation
- On-board memory stores last set speed
- ¼ turn bayonet probe mounting for fast release
- Compatible with Omni Tip™ disposable probes, hybrid Omni Tip™ probes and stainless steel generator probes
- Light weight ergonomic design
- 3-year motor warranty
- Speed is adjustable in 500 rpm increments from 8,000 to 32,000 rpm



Shown with
optional Stand
Assembly
(Order #S1000)

Omni TH_Q Digital Hand-held Tissue Homogenizer

Includes TH_Q motor, clamp for stand mounting, 6 Hard and 6 Soft Omni Tip™ Disposable Generator Probes, tool kit, post-clamp motor mount, instruction manual and storage case. *Stainless steel generator probes sold separately*

Description	Order #
Omni TH _Q Digital Handheld Tissue Homogenizer (universal voltage)	12-500



ROTOR-STATOR HOMOGENIZERS

Omni Tip™ Disposable Generator Probes ///

Compatible with TH*, µHb, TH_Q, GLH*, Omni Prep, Prep 96 and LH 96

Patented **Omni Tip™ Generator Probes** are designed to completely avoid cross-contamination between samples. They are engineered from a durable plastic and come in two different configurations for soft tissue and hard tissue. Designed for research involving critical samples at very small volumes, they prevent sample loss with a unique two-piece design and the clear stator tube. These tips are economical to allow for disposal after each use or they can be cleaned and autoclaved up to seven times. Omni Tips™ offer a cost effective solution for customers processing highly sensitive samples where contaminants can affect test results.

PRODUCT FEATURES:

- Eliminate cross-contamination by disposal after use
- Ideal for PCR, DNA and RNA blot analysis
- Reusable and autoclavable up to 7 times (at 250°F/121°C) *

(Note: Polycarbonate outer tube can be compromised when using harsh reagents/solvents. May limit the number of times the Omni Tip™ can be reused. Factors such as sample type, volume and reagent will determine number of uses.)

- Simple two piece construction for very easy cleaning
- Clear stator tube assures that valuable sample is not trapped or lost in probe
- 80% less protein residue after cleaning than with stainless steel generator probes
- Fraction of the cost of stainless steel generator probes
- Ideal and cost effective for processing multiple samples
- Outer tube comprised of polycarbonate and inner shaft made of Ultem *

(Note: Polycarbonate outer tube can be compromised when using harsh reagents/solvents. May limit the number of times the Omni Tip™ can be reused. Factors such as sample type, volume and reagent will determine number of uses.)

(Note: Omni Tip Adaptor (Order #A1000SB) required to use Omni Tips with TH, GLH and PDH.)



Omni Tip™ Plastic Probes
Patent #6,398,402
Patent #6,863,431

Omni Deaggregation Tips (7 mm diameter x 110 mm length)

For processing liquids, soft tissues, and samples that require gentle processing

Description	Order #
25 Omni Deaggregation Tips	30750
50 Omni Deaggregation Tips	32750
100 Omni Deaggregation Tips	34750
500 Omni Deaggregation Tips	35750
1,000 Omni Deaggregation Tips	3M750

Omni Hard Tissue Tips (7 mm diameter x 110 mm length)

For processing hard or frozen tissue samples

Description	Order #
25 Omni Hard Tissue Tips	30750H
50 Omni Hard Tissue Tips	32750H
100 Omni Hard Tissue Tips	34750H
500 Omni Hard Tissue Tips	35750H
1,000 Omni Hard Tissue Tips	3M750H



Omni Tip™ Disposable Generator Probes ///

Compatible with TH*, μHb, TH_Q, GLH*, Omni Prep, Prep 96 and LH 96



The **Omni Tip™ Hybrid Probes** combine the convenience of disposable generator probes with the durability of traditional stainless steel probes. Hybrid probes are made up of an outer stainless steel tube with an inner Ultem™ plastic shaft. The plastic shafts can either be disposed of after use or cleaned and reused multiple times. The simple two-piece design makes these probes much easier to clean and disassemble than traditional stainless steel probes.

Description	Processing Range	Order #
7 mm x 110 mm Hybrid Probe	0.2 mL - 30 mL	22-007
7 mm x 110 mm Hybrid Probes (6 pack)	0.2 mL - 30 mL	22-007-6
Replacement Shafts (25 pack)	0.2 mL - 30 mL	301725HT

Sealed Conical and Flat Bottom Tubes - *Omni Tips™ not included*



Polypropylene conical bottom tubes with sealed caps are compatible with Omni Tip™ disposable generator probes to reduce aerosoling during the homogenization process. Tube caps contain a hole for insertion of the Omni Tip into the tube.

Description	Order #
15 mL Plastic Conical Bottom Tubes with Sealed Caps (25 pack)	00-2015-25
50 mL Plastic Conical Bottom Tubes with Sealed Caps (25 pack)	00-2050-25
4 mL Glass Flat Bottom Tubes with Sealed Caps (25 pack)	00-2004-25
8 mL Glass Flat Bottom Tubes with Sealed Caps (25 pack)	00-2008-25

Omni Tip™ Adaptor



Required when using Omni Tips™ with the Omni TH, GLH and PDH Homogenizers

Description	Order #
Omni Tip Adaptor	A10005B



ROTOR-STATOR HOMOGENIZERS

Powerful Laboratory Homogenizer ///

OMNI GLH — General Lab Homogenizer

The **Omni GLH** is a powerful, versatile, and durable homogenizer that can handle virtually any processing application. Its high power motor can handle even the toughest tissue samples, and emulsions and dispersions are quickly and easily completed. The Omni GLH is compatible with stainless steel generator probes and Omni Tip™ disposable probes when used in conjunction with the A1000SB Omni Tip™ Adaptor. It has a processing range of 0.20 mL to 10 liters, which makes it one of the most flexible homogenizers available. We recommend stand mounting the GLH.

PRODUCT FEATURES: CE

- Powerful 700 watt motor with variable motor speed control from 5,000 to 28,000 rpm
- Compatible with 5, 7, 10, 20, 32 and 35 mm diameter stainless steel generator probes & Omni Tip™ disposable probes (with an Omni Tip™ Adaptor)
- Process sample volumes of 0.20 mL to 10 L
- ¼ turn bayonet probe mounting system for quick connection and release of generator probes
- Ideal for longer processing cycles
- 1-year motor warranty



Shown with optional Stand Assembly (Order #S1000)

Omni GLH General Lab Homogenizer

Includes 700 watt motor, tool kit, cross rod and stand clamp for mounting and instruction manual. *Omni Tips™ and Stainless Steel Generator Probes sold separately*

Description	Order #
115V Omni GLH: General Lab Homogenizer (motor only)	GLH-115
220V Omni GLH: General Lab Homogenizer (motor only)	GLH-220

Omni GLH Homogenizer Package

Includes GLH Motor, 3 Stainless Steel Generator Probes (10 x 195 mm saw tooth, 20 x 195 mm saw tooth, 35 x 195mm flat bottom) and Motor Stand Assembly (Order #S1000)

Description	Order #
115V Complete GLH Package	GLHP-115
220V Complete GLH Package	GLHP-220

GLH Accessories

Stand Assembly For post-mounted operation

Description	Order #
Optional Motor Stand Assembly	S1000

Vessel Restraint Disk

The Vessel Restraint Disk can be used to help reduce splashing and contain aerosols during homogenization. This accessory is compatible with 20mm and larger diameter rotor-stator generator probes and with containers up to six inches in diameter. It also helps secure the container during processing. *Note: The Vessel Restraint Disk will not create an air-tight seal. Proper safety measures are necessary when working with dangerous samples.*

Description	Order #
Vessel Restraint Disk	LT-750

Can also be used with the PDH





Powerful Laboratory Homogenizer ///

OMNI PDH — Programmable Digital Homogenizer

The **Omni PDH** is a programmable 700 watt motor unit. The digital speed display allows for reproducibility and ease of use. The PDH is a powerful, versatile, and durable homogenizer that can handle virtually any processing application. Its high power motor can handle even the toughest tissue samples, and emulsions and dispersions are quickly and easily completed. The Omni PDH is compatible with stainless steel generator probes and Omni Tip™ disposable probes when used in conjunction with the A1000SB Omni Tip™ Adaptor. It has a processing range of 0.20 mL to 10 liters, which makes it one of the most flexible homogenizers available.

PRODUCT FEATURES: CE

- Compatible with 5 mm, 7 mm, 10 mm, 20 mm, 32 mm and 35 mm stainless steel generator Probes & Omni Tip™ disposable probes (with an Omni Tip™ Adaptor)
- Powerful 700 watt motor
- Ideal for lab automation, pilot scale or small batch applications
- Speed control from 1,000 to 28,000 rpm maintains constant speed over wide operating range for accurate (+/- 0.5%) repeatability
- Store up to 12 programs with multiple speed, time, and ramp functions
- 32 digit alpha numeric display
- 1-year motor warranty
- Movable platform stand
- Process sample volumes of 0.2 mL-10 L



Omni PDH Programmable Digital Homogenizer

Includes 700 watt motor, motor stand assembly, tool kit and instruction manual.

Omni Tips™ and Stainless Steel Generator Probes sold separately

Description	Order #
115V Omni PDH: Programmable Digital Homogenizer (motor only)	PDH-115
220V Omni PDH: Programmable Digital Homogenizer (motor only)	PDH-220

Omni PDH Homogenizer Package

Includes PDH Motor, 3 Stainless Steel Generator Probes (10 x 195 mm saw tooth, 20 x 195 mm saw tooth, 35 x 195mm flat bottom) and Motor Stand Assembly

Description	Order #
115V Complete PDH Package	PDHP-115
220V Complete PDH Package	PDHP-220



ROTOR-STATOR HOMOGENIZERS

Stainless Steel Generator Probes ///

Compatible with Omni GLH & PDH Homogenizers



Stainless Steel Homogenizer Probes for GLH & PDH Homogenizers

All generator probes are available in Titanium and custom sizes. Call for pricing.

Omni Homogenizer	Diameter	Processing Range	Recommended Vessel Size	Length	Type	Resulting Particle Size	Order #
Omni TH (TH115/220)	5 mm	0.20 mL - 5 mL	Vessel with a minimum inner diameter of 6 mm	75 mm	Flat bottom	Fine	G5-75
					Flat bottom - Wide Window	Coarse	G5-75W
	7 mm	0.25 mL - 30 mL	Vessel with a minimum inner diameter of 8 mm	95 mm	Flat bottom	Fine	G7-95
					Flat bottom - Wide Window	Coarse	G7-95W
					Saw Tooth	Fine	G7-95ST
					Saw Tooth - Wide Window	Coarse	G7-95STW
					Flat bottom	Fine	G7-195
					Flat bottom - Wide Window	Coarse	G7-195W
	10 mm	1.5 mL - 100 mL	Vessel with a minimum inner diameter of 12.5 mm	195 mm	Saw Tooth	Fine	G7-195ST
					Saw Tooth - Wide Window	Coarse	G7-195STW
					Saw Tooth	Fine	G10-95
					Saw Tooth - Wide Window	Coarse	G10-95W
20 mm	50 mL - 2 L	Vessel with a minimum inner diameter of 22 mm	195 mm	Saw Tooth	Fine	G10-195	
				Saw Tooth - Wide Window	Coarse	G10-195W	
32 mm	75 mL - 10 L	Vessel with a minimum inner diameter of 35 mm	195 mm	Saw Tooth	Fine	G20-195ST	
				Saw Tooth - Wide Window	Coarse	G20-195STW	
35 mm	75 mL - 10 L	Vessel with a minimum inner diameter of 37 mm	195 mm	Tablet Processing	Tablet Processing	G32TT-195	
				Flat bottom	Fine	G35NA-195	
					Flat bottom - Wide Window	Coarse	G35WA-195

Stainless Steel Homogenizer Probe Disassembly Tool Kit

For use with generator probes listed above

Description	Order #
Stainless Steel Homogenizer Probe Disassembly Tool Kit	T1001



High Power Homogenizer ///

OMNI Mixer Homogenizing Systems

Omni Mixer and **Omni Macro** Homogenizers offer the perfect mix of dependability, versatility and power. Sealed containers are available in a variety of materials (stainless steel, glass & plastic). Interchangeable blades and rotor-stator generators process a wide range of samples within the same container. Process sample volumes ranging from 0.25 mL to 30 L with speeds ranging from 500 to 20,000 rpm.

PRODUCT FEATURES: CE

- 3-year motor warranty
- Powerful 600 or 1,800 watt motor
- Variable speed control 500 to 20,000 rpm
- Quiet operation
- Accessories include generator probes, cutting blades, and sealed chambers
- Accessories are compatible with all Omni Mixers built within the last 60 years



Omni Mixer Homogenizer

Includes motor with variable speeds, motor stand assembly, generator probe adapter, tool kit and instruction manual.

*Aerosol Sealed Chambers and Generator Probes sold separately.**

- 600 watt motor with variable speeds from 500 to 18,000 rpm
- For processing 0.25 mL-10 L

Description	Order #
115V Omni Mixer Homogenizer	17105
220V Omni Mixer Homogenizer	17106

Omni Macro Homogenizer

Includes motor with variable speeds, motor stand assembly, generator probe adapter, tool kit and instruction manual. *Aerosol Sealed Chambers and Generator Probes sold separately.**

- 1,800 watt motor with variable speeds from 1,000 to 20,000 rpm
- For processing 0.25 mL-30 L

Description	Order #
115V Omni Macro Homogenizer	17505
220V Omni Macro Homogenizer	17506



ROTOR-STATOR HOMOGENIZERS

Programmable High Power Homogenizer ///

OMNI MACRO-ES — Programmable Digital High Power Homogenizer

The **Omni Macro-ES** Homogenizer is a programmable, 1,800 watt motor unit. It offers the perfect mix of programmability, versatility, and power. The digital speed display allows for additional reproducibility.

PRODUCT FEATURES: CE

- Compatible with all Omni Mixer Accessories
- Powerful 1,800 watt motor
- Quick Connect coupling assembly included
- Ideal for lab automation, pilot scale or small batch applications
- Speed control from 1,000 to 20,000 rpm maintains constant speed over wide operating range for accurate (+/- 0.5%) repeatability
- Store up to 12 programs with multiple speed, time and ramp functions
- 32 digit alpha numeric display
- Movable platform stand
- 3-year motor warranty



Omni Macro-ES Programmable Homogenizer

Includes 1,800 watt motor with variable speeds, motor stand assembly, Quick Connect coupling assembly, 2 Quick Connect Adapters, generator probe adapter, tool kit and instruction manual. *Chamber Assemblies and Generator Probes sold separately.**

Description	Order #
115V Omni Macro-ES Homogenizer	MES-115
220V Omni Macro-ES Homogenizer	MES-220

Omni Macro-ES Homogenizer Package

Includes Macro-ES and 3 Stainless Steel Generator Probes (20 x 195 mm saw tooth, 35 x 195 mm flat bottom, 45 x 195mm flat bottom)

Description	Order #
115V Complete Macro-ES Package	MESP-115
220V Complete Macro-ES Package	MESP-220





Stainless Steel Generator Probes ///

Designed for Omni Mixer, Macro & Macro-ES Homogenizers



Stainless Steel Homogenizer Probes

All generator probes are available in Titanium and custom sizes. Call for pricing.

Omni Homogenizer	Diameter	Processing Range	Recommended Vessel Size	Length	Type	Resulting Particle Size	Order #						
Omni Mixer (17105/17106)	7 mm	0.25 mL - 30 mL	Vessel with a minimum inner diameter of 8 mm	95 mm	Flat bottom	Fine	15007						
					Flat bottom - Wide Window	Coarse	15007W						
					Saw Tooth bottom	Fine	15007ST						
				195 mm	Saw Tooth - Wide Window	Coarse	15007STW						
					Flat bottom	Fine	15007L						
					Flat bottom - Wide Window	Coarse	15007LW						
	Omni Macro (17505/17506)	10 mm	1.5 mL - 100 mL	Vessel with a minimum inner diameter of 12.5 mm	95 mm	Saw Tooth	Fine	15051					
						Saw Tooth - Wide Window	Coarse	15051W					
					195 mm	Saw Tooth	Fine	15010					
						Saw Tooth - Wide Window	Coarse	15010W					
						Omni Macro-ES (MES-115/220)	20 mm	50 mL - 2 L	Vessel with a minimum inner diameter of 22 mm	100 mm	Saw Tooth	Fine	15201
											Saw Tooth - Wide Window	Coarse	15201W
145 mm	Saw Tooth	Fine	15401										
	Saw Tooth - Wide Window	Coarse	15401W										
195 mm	Saw Tooth	Fine	15020										
	Saw Tooth - Wide Window	Coarse	15020W										
32 mm	75 mL - 10 L	Vessel with a minimum inner diameter of 35 mm	195 mm	Tablet Processing	Tablet Processing	150-32TT-195							
35 mm	75 mL - 10 L	Vessel with a minimum inner diameter of 37 mm	195 mm	Flat bottom	Fine	150-32NA-195							
				Flat bottom - Wide Window	Coarse	150-35WA-195							
45 mm	200 mL - 25 L	Vessel with a minimum inner diameter of 47 mm	195 mm	Flat bottom	Fine	150-45NA-195							
				Flat bottom - Wide Window	Coarse	150-45WA-195							
55 mm	300 mL - 30 L	Vessel with a minimum inner diameter of 57 mm	195 mm	Flat bottom	Fine	150-55NA-195							
				Flat bottom - Wide Window	Coarse	150-55WA-195							

Generator Probe Accessories

Description	Order #
Stainless Steel Homogenizer Probe Disassembly Tool Kit	17104
Generator Probe Adapter (one adapter is included with each motor)	15001



ROTOR-STATOR HOMOGENIZERS

Omni Mixer Accessories ///

For use with Omni Mixer, Macro & Macro-ES Homogenizers



Quick Connect (QC) Coupling Assembly for Omni Mixer, Macro, Macro ES

The Quick Connect Assembly makes the Omni Mixer homogenizers even more convenient to use. It comes standard on the Omni Macro-ES. To use, attach a Quick Connect Adapter to your chamber assembly or generator probe. Next, slide the Adapter into the Quick Connect Coupling and a retaining ring positions into place for a secure hold. To disconnect, simply slide the ring upward and the processing accessory is conveniently released.

Description	Order #
Quick Connect Kit (includes QC Assembly and 3 QC Adapters)	17215
Quick Connect Coupling (Requires one per motor unit)	17210
Quick Connect Adapter (Requires one per generator or accessory)	17204



Vessel Restraint Disk

The Vessel Restraint Disk can be used to help reduce splashing and contain aerosols during homogenization. This accessory is compatible with 20 mm and larger diameter rotor-stator generator probes and with containers up to six inches in diameter. It also helps secure the container during processing. * Note: Not designed to completely contain aerosols.

Description	Order #
Vessel Restraint Disk	LT-750



Micro-Homogenizer Attachment (MHA)

The Micro-Homogenizer Attachment converts your Omni Mixer, Omni Macro or Omni Macro-ES into a Micro-Sample Homogenizer. Sample volume ranges from 0.5 to 5 mL with your choice of either a Stainless Steel or Nylon Insert Chamber.

Description	Order #
MHA with Stainless Steel Chamber	18074
MHA with 12 each Nylon Chambers	18073
Spare Stainless Steel Chamber	18060
12 Spare Nylon Inserts	18068



Aerosol Sealed Stainless Steel Chamber Assemblies ///

For use with Omni Mixer, Macro & Macro-ES Homogenizers

Custom configurations are also available. *Call for pricing.*

Note: Sealed chamber assemblies are a secondary means of protection. Always use the appropriate safety measures when processing pathogens.

PRODUCT FEATURES:

- Fluted to reduce circular flow and enhance processing
- Polished interior to facilitate cleaning
- Available in Titanium



50 mL Sealed Stainless Steel Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 1-inch Cutting Blade	13 mL - 50 mL	17077
Oilite Bearings and 1-inch Cutting Blade	13 mL - 50 mL	17061
10 mm diameter generator probe for fine to medium particle sizes	15 mL - 50 mL	15050
10 mm diameter generator probe for medium to coarse particle sizes	15 mL - 50 mL	15050W



200 mL Sealed Stainless Steel Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	80 mL - 200 mL	17078
Oilite Bearings and 2-inch Cutting Blade	80 mL - 200 mL	17062
20 mm diameter generator probe for fine to medium particle sizes	100 mL - 200 mL	15200
20 mm diameter generator probe for medium to coarse particle sizes	100 mL - 200 mL	15200W



400 mL Sealed Stainless Steel Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	90 mL - 400 mL	17079
Oilite Bearings and 2-inch Cutting Blade	90 mL - 400 mL	17063
20 mm diameter generator probe for fine to medium particle sizes	100 mL - 400 mL	15400
20 mm diameter generator probe for medium to coarse particle sizes	100 mL - 400 mL	15400W



ROTOR-STATOR HOMOGENIZERS

Aerosol Sealed Glass Chamber Assemblies ///

For use with Omni Mixer, Macro & Macro-ES Homogenizers

Note: Sealed chamber assemblies are a secondary means of protection. Always use the appropriate safety measures when processing pathogens.

PRODUCT FEATURES:

- Allows you to view sample while processing



50 mL Sealed Glass Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 1-inch Cutting Blade	25 mL - 50 mL	17064
10 mm diameter generator probe for fine to medium particle sizes	25 mL - 50 mL	15064
10 mm diameter generator probe for medium to coarse particle sizes	25 mL - 50 mL	15064W



200 mL Sealed Glass Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 1-inch Cutting Blade	40 mL - 150 mL	17088
20 mm diameter generator probe for fine to medium particle sizes	40 mL - 150 mL	15088
20 mm diameter generator probe for medium to coarse particle sizes	40 mL - 150 mL	15088W



473 mL Sealed Glass Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	175 mL - 350 mL	17080
Oilite Bearings and 2-inch Cutting Blade	175 mL - 350 mL	17083
20 mm diameter generator probe for fine to medium particle sizes	150 mL - 350 mL	15080
20 mm diameter generator probe for medium to coarse particle sizes	150 mL - 350 mL	15080W

946 mL Sealed Glass Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	225 mL - 700 mL	17081
Oilite Bearings and 2-inch Cutting Blade	225 mL - 700 mL	17084
20 mm diameter generator probe for fine to medium particle sizes	200 mL - 700 mL	15081
20 mm diameter generator probe for medium to coarse particle sizes	200 mL - 700 mL	15081W



Aerosol Sealed Plastic Chamber Assemblies ///

For use with Omni Mixer, Macro & Macro-ES Homogenizers

Note: Sealed chamber assemblies are a secondary means of protection. Always use the appropriate safety measures when processing pathogens.

PRODUCT FEATURES:

- Economical chambers are virtually unbreakable.



50 mL Sealed Polycarbonate Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 1-inch Cutting Blade	10 mL - 25 mL	17076
10 mm diameter generator probe for fine to medium particle sizes	12 mL - 25 mL	15076
10 mm diameter generator probe for medium to coarse particle sizes	12 mL - 25 mL	15076W



250 mL Sealed Polycarbonate Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 1-inch Cutting Blade	50 mL - 200 mL	17089
20 mm diameter generator probe for fine to medium particle sizes	65 mL - 200 mL	15089
20 mm diameter generator probe for medium to coarse particle sizes	65 mL - 200 mL	15089W



473 mL Sealed Polycarbonate Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	175 mL - 375 mL	17065
20 mm diameter generator probe for fine to medium particle sizes	180 mL - 375 mL	15065
20 mm diameter generator probe for medium to coarse particle sizes	180 mL - 375 mL	15065W



946 mL Sealed Polycarbonate Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	250 mL - 800 mL	17097
20 mm diameter generator probe for fine to medium particle sizes	275 mL - 800 mL	15097
20 mm diameter generator probe for medium to coarse particle sizes	275 mL - 800 mL	15097W

1892 mL Sealed Polycarbonate Chamber Assembly

Description	Processing Range	Order #
PTFE Bearings and 2-inch Cutting Blade	400 mL - 1350 mL	17098
20 mm diameter generator probe for fine to medium particle sizes	450 mL - 1350 mL	15098
20 mm diameter generator probe for medium to coarse particle sizes	450 mL - 1350 mL	15098W



ROTOR-STATOR HOMOGENIZERS

Generator Probe Selection Guide ///

For all Omni Rotor-Stator Homogenizers

Omni Homogenizer	Part Number	VOLUME RANGE								Diameter	Length
		10 mL	50 mL	100 mL	500 mL	2 L	10 L	25 L	50 L		
Omni TH (TH115/220) GLH (GLH-115/220) PDH (PDH-115/220)	G5-75	█								5 mm	75 mm
	G5-75W	█								5 mm	75 mm
	G7-95	█	█							7 mm	95 mm
	G7-95W	█	█							7 mm	95 mm
	G7-95ST	█	█							7 mm	95 mm
	G7-95STW	█	█							7 mm	95 mm
	G7-195	█	█							7 mm	195 mm
	G7-195W	█	█							7 mm	195 mm
	G7-195ST	█	█							7 mm	195 mm
	G7-195STW	█	█							7 mm	195 mm
	G10-95	█	█	█						10 mm	95 mm
	G10-95W	█	█	█						10 mm	95 mm
	G10-195	█	█	█						10 mm	195 mm
	G10-195W	█	█	█						10 mm	195 mm
	Omni Mixer (17105/17106) Omni Macro (17505/17506) Omni Macro-ES (MES-115/MES-220)	G20-195ST			█	█					20 mm
G20-195STW				█	█					20 mm	195 mm
G-32TT-195				█	█	█				32 mm	195 mm
G-35NA-195				█	█	█				35 mm	195 mm
G-35WA-195				█	█	█				35 mm	195 mm
15007		█	█							7 mm	95 mm
15007W		█	█							7 mm	95 mm
15007ST		█	█							7 mm	95 mm
15007STW		█	█							7 mm	95 mm
15007L		█	█							7 mm	195 mm
15007LW	█	█							7 mm	195 mm	
15007LST	█	█							7 mm	195 mm	
15007LSTW	█	█							7 mm	195 mm	
15051	█	█	█						10 mm	95 mm	
15051W	█	█	█						10 mm	95 mm	
15010	█	█	█						10 mm	195 mm	
15010W	█	█	█						10 mm	195 mm	
15201			█	█	█				20 mm	100 mm	
15201W			█	█	█				20 mm	100 mm	
15401			█	█	█				20 mm	145 mm	
15401W			█	█	█				20 mm	145 mm	
15020			█	█	█				20 mm	195 mm	
15020W			█	█	█				20 mm	195 mm	
150-32TT-195			█	█	█	█			32 mm	195 mm	
150-35NA-195			█	█	█	█			35 mm	195 mm	
150-35WA-195			█	█	█	█			35 mm	195 mm	
150-45NA-195				█	█	█	█		45 mm	195 mm	
150-45WA-195				█	█	█	█		45 mm	195 mm	
150-55NA-195					█	█	█	█	55 mm	195 mm	
150-55WA-195					█	█	█	█	55 mm	195 mm	
Omni µHb (H115/H220) Omni TH ₀ (12-200) Omni TH _B (THB-01) Omni Prep (06-021)	B5-075	█								5 mm	75 mm
	B7-110ST	█	█							7 mm	110 mm
	B10-110ST	█	█	█						10 mm	110 mm
	22-007	█	█							7 mm	110 mm
	30750	█	█							7 mm	110 mm
	30750H	█	█							7 mm	110 mm



Chamber Selection Guide ///

For Omni Mixers, Macro and Macro-ES Homogenizers

Chamber Material	Part Number	VOLUME RANGE					Bearings	Disperser		
		10 mL	50 mL	100 mL	500 mL	750 L				
Stainless Steel	17077		■					PTFE	1-inch Cutting Blade	
	17061		■					Oilite	1-inch Cutting Blade	
	15050		■						10 mm diameter generator probe for fine to medium particles	
	15050W		■						10 mm diameter generator probe for medium to coarse particles	
	17078			■	■			PTFE	2-inch Cutting Blade	
	17062			■	■			Oilite	2-inch Cutting Blade	
	15200			■	■				20 mm diameter generator probe for fine to medium particles	
	15200W			■	■				20 mm diameter generator probe for medium to coarse particles	
	17079				■	■		PTFE	2-inch Cutting Blade	
	17063				■	■		Oilite	2-inch Cutting Blade	
	15400				■	■			20 mm diameter generator probe for fine to medium particles	
	15400W				■	■			20 mm diameter generator probe for medium to coarse particles	
	Glass	17064		■					PTFE	1-inch Cutting Blade
		15064		■						10 mm diameter generator probe for fine to medium particles
15064W			■						10 mm diameter generator probe for medium to coarse particles	
17088				■	■			PTFE	1-inch Cutting Blade	
15088				■	■				20 mm diameter generator probe for fine to medium particles	
15088W				■	■				20 mm diameter generator probe for medium to coarse particles	
17080					■	■		PTFE	2-inch Cutting Blade	
17083					■	■		Oilite	2-inch Cutting Blade	
15080					■	■			20 mm diameter generator probe for fine to medium particles	
15080W					■	■			20 mm diameter generator probe for medium to coarse particles	
17081						■	■	PTFE	2-inch Cutting Blade	
17084						■	■	Oilite	2-inch Cutting Blade	
15081						■	■		20 mm diameter generator probe for fine to medium particles	
15081W						■	■		20 mm diameter generator probe for medium to coarse particles	
Plastic	17076		■					PTFE	1-inch Cutting Blade	
	15076		■						10 mm diameter generator probe for fine to medium particles	
	15076W		■						10 mm diameter generator probe for medium to coarse particles	
	17089			■	■			PTFE	1-inch Cutting Blade	
	15089			■	■				20 mm diameter generator probe for fine to medium particles	
	15089W			■	■				20 mm diameter generator probe for medium to coarse particles	
	17065				■	■		PTFE	2-inch Cutting Blade	
	15065				■	■			20 mm diameter generator probe for fine to medium particles	
	15065W				■	■			20 mm diameter generator probe for medium to coarse particles	
	17097					■	■	PTFE	2-inch Cutting Blade	
	15097					■	■		20 mm diameter generator probe for fine to medium particles	
	15097W					■	■		20 mm diameter generator probe for medium to coarse particles	
	17098						■	PTFE	2-inch Cutting Blade	
	15098						■		20 mm diameter generator probe for fine to medium particles	
15098W						■	45 mm	20 mm diameter generator probe for medium to coarse particles		



ROTOR-STATOR HOMOGENIZERS

Omni Prep 6-sample Homogenizer ///

The **Omni Prep 6-Sample Homogenizer** is designed to streamline the labor and time intensive homogenization process. It features a brushless motor that is virtually maintenance free, is ultra quiet during operation, and uses about 10% of the power required to process 6 samples individually.

An oscillating sample rack holds up to 6 tubes from 1.5 mL to 50 mL in size and emulates hand processing. Microprocessor control allows the user to program time (up to 10 minutes) and speed (500 - 30,000 rpm). Sample volumes of 0.25 mL to 50 mL can be homogenized using 5, 7 or 10 mm stainless steel generator probes or with Omni Tip™ disposable generator probes.

Omni Tips can be used to completely eliminate cross-contamination as well as the time consuming cleaning step associated with the use of stainless steel generator probes.



PRODUCT FEATURES: CE

- Process 6 samples per cycle and up to 250 samples per hour
- Utilizes Omni Tip™ Generator Probes
- Compatible with stainless steel generator probes from 5 to 10 mm
- Microprocessor controlled with 3 stored programs
- Speed Control from 500 to 30,000 rpm
- Process most samples in less than 1 minute
- Positive airflow that can be exhausted to a HEPA-filter or Fume Hood
- Sealed and open vessel processing configurations
- Oscillating (up/down) rack for efficient processing of all size samples
- Clear door allows sample viewing and prevents splashing
- Optional ice tray for frozen samples
- Compact design: 15.7in. (40cm) x 7.8 in. (20cm) x 11.8 in. (30cm)
- 1-year motor warranty

Omni Prep 6-Sample Homogenizer

Includes Omni Prep Motor Drive Unit and User Manual.

Description	Order #
Omni Prep Homogenizer	06-021

The Omni Prep is sold as a customizable homogenizing system. Please see the following pages to choose the accessories best suited for your processing needs.

At least 1 processing rack, 3 tube holders and Omni Tips™ are required to operate the Omni Prep.



Omni Prep Accessories ///

Omni Prep Processing Rack

Movable for highly efficient processing. *Required for operating the Omni Prep.*

Description	Order #
Processing Rack for Omni Prep	06-220



Rack Tube Holder

Tube holders are available for 1.5-2 mL, 5 mL, 15 mL and 50 mL sample tubes. Custom tube holder size are also available. Each holder holds 2 samples tubes, therefore a total of 3 tube holders must be purchased. *Required for operating the Omni Prep.*


Description	Order #
Rack Tube Holder for 1.5 - 2 mL	06-209-02
Rack Tube Holder for 5 mL	06-209-05
Rack Tube Holder for 15 mL	06-209-15
Rack Tube Holder for 50 mL	06-209-50



Ice Tray

Keeps frozen and sensitive samples cold during processing. *Rack sold separately.*

Description	Order #
Ice Tray for 1.5 mL-2 mL Tubes	06-207
Ice Tray for 15 mL-50 mL Tubes	06-210





ROTOR-STATOR HOMOGENIZERS

Omni Prep Generator Probes ///

Stainless Steel Generator Probes



Description	Order #
5mm X 75mm Stainless Steel Probe	B5-075
5mm X 75mm Stainless Steel Probes (6 Pack)	B5-075-6
7mm X 110mm Stainless Steel Probe	B7-110ST
7mm X 110mm Stainless Steel Probes (6 Pack)	B7-110ST-6
10mm X 110mm Stainless Steel Probe	B10-110ST
10mm X 110mm Stainless Steel Probes (6 Pack)	B10-110ST-6

7 mm Omni Tip™ Hybrid Generator Probes



The **Omni Tip™ Hybrid Probes** combine the convenience of disposable generator probes with the durability of traditional stainless steel probes. Hybrid probes are made up of an outer stainless steel tube with an inner Ultem™ plastic shaft. The plastic shafts can either be disposed of after use or cleaned and reused multiple times. The simple two-piece design makes these probes much easier to clean and disassemble than traditional stainless steel probes.

Description	Order #
7 mm x 110 mm Hybrid Probe	22-007
7 mm x 110 mm Hybrid Probes (6 pack)	22-007-6
Replacement Shafts (25 pack)	301725HT

Omni Tips™

Omni Deaggregation Tips (7 mm diameter x 110 mm length)

For processing liquids, soft tissues, and samples that require gentle processing



Description	Order #
25 Omni Deaggregation Tips	30750
50 Omni Deaggregation Tips	32750
100 Omni Deaggregation Tips	34750
500 Omni Deaggregation Tips	35750
1,000 Omni Deaggregation Tips	3M750

Omni Hard Tissue Tips (7 mm diameter x 110 mm length)

For processing hard or frozen tissue samples



Description	Order #
25 Omni Hard Tissue Tips	30750H
50 Omni Hard Tissue Tips	32750H
100 Omni Hard Tissue Tips	34750H
500 Omni Hard Tissue Tips	35750H
1,000 Omni Hard Tissue Tips	3M750H



Omni Prep 96 ///

AUTOMATED HOMOGENIZER WORKSTATION

The **Omni Prep 96** is a fully automated sample prep homogenizer workstation designed to eliminate bottlenecks and increase throughput in your lab. Its modular and robust design enables walk away processing of up to 96 samples per batch.

The small footprint of the Prep 96 saves valuable bench top space, and will also fit into most standard bio safety cabinets and fume hoods. The User Interface makes it easy for you to program, save, recall or make changes to existing protocols. The latter ability allows for repeatable results while minimizing the element of human error.

PRODUCT FEATURES:

- Walk away automated homogenization
- Reduce the risk of cross contamination
- Increase throughput
- Get consistent results, every time
- Compatible with Omni Tips™, Hybrid and stainless steel generator probes
- Low noise, high repeatability
- Process 4 samples simultaneously; 24 to 96 samples, depending on tube size



Omni Prep 96 Automated Homogenizer

Omni Prep 96 comes standard with four 40-watt brushless motors, 1 control box, PC, operating software, (1) 96 place Sample Tube Rack, and (10) 96 place Tip holder rack.

Description	Order #
Omni Prep 96 Homogenizer Workstation	51-001-1

Omni Prep 96 Accessories

Description	Order #
Prep 96 Tip Holder Rack	51-HWR-13
Ultrasonic Bath	51-HWR-08
Sample Tube Holder Rack	51-HWR-11



ROTOR-STATOR HOMOGENIZERS

Omni LH 96 ///

LIQUID HANDLING HOMOGENIZER WORKSTATION

The **Omni LH 96** combines multiple sample prep steps into one versatile, efficient and automated device. Quite literally, what used to take hours can now be completed in a matter of minutes.

This product delivers significantly improved performance in the lab, while saving valuable time and greatly reducing costs related to labor intensive processes. No other device can match the versatility and power of the LH96.


The LH 96 combines a core homogenizing platform, capable of efficiently processing a wide variety of samples, with a fully integrated liquid handling option.

The workstation is compatible with patented Omni Tip™ disposable homogenizing probes, designed to completely avoid cross-contamination between samples during homogenization.

The LH 96 can automatically dispense buffer or diluents based on user defined specifications or actual sample weight. Four independent pipette channels transfer homogenate to 96-well plates or other tube formats.

Bar Code Reader and Automatic Sample Weighing are also available for the LH 96. Integrated sample cooling down to 4°C is also available for those working with frozen and/or delicate samples.

The LH 96 is an ideal instrument for any lab looking to automate processes, especially those who are performing medium to high throughput tissue homogenization.



PRODUCT FEATURES:

- Replace your homogenizer, liquid handler, pipette & weighing platform, all in one automated machine
- Speed up your sample prep
- Reduce space in the lab
- Eliminate risk of cross contamination
- Get consistent results, every time
- Walkaway processing
- Fits in a fume hood
- Barcode reading

Omni LH 96 Automated Homogenizer

Includes 8-sample homogenization platform. Customize by choosing from the following options: Liquid Handling/Automated Sample Transfer, Automated Pipetting, Bar Code Scanning, Sample Weighing and Sample Cooling (Active or Passive)

Description	Order #
Omni LH 96 Homogenizer Workstation	Call for ordering info



System Specifications ///



OMNI PREP 96



OMNI LH 96

Application	Homogenizer only	Homogenizer plus liquid handling
Graphical User Interface (GUI)	PC-based software with GUI. Programs may be customized and stored for rapid call up.	PC-based software with GUI. Programs may be customized and stored for rapid call up.
Sample Capacity	8 samples simultaneously. 24 to 96 samples, depending on tube size.	8 samples simultaneously. 24 to 96 samples, depending on tube size.
Tube Size	2 mL, 5 mL, 14 mL, 15 mL, 20 mL, 35 mL and 50 mL**	2 mL, 5 mL, 14 mL, 15 mL, 20 mL, 35 mL and 50 mL**
Processing Range	.25 mL to 35 mL per tube*	.25 mL to 35 mL per tube*
Generator Probes	Omni Tip™ disposable probes. Hard or soft tissue version. 7 mm x 110 mm length. Omni Tip™ Hybrid probes with stainless steel exterior stator shaft and plastic interior rotor for added versatility. Stainless steel probes (5, 7, or 10 mm diameter) may also be used.	Omni Tip™ disposable probes. Hard or soft tissue version. 7 mm x 110 mm length. Omni Tip™ Hybrid probes with stainless steel exterior stator shaft and plastic interior rotor for added versatility. Stainless steel probes (5, 7, or 10 mm diameter) may also be used.
Cleaning Bath (Optional)	3 stage cleaning bath (for cleaning stainless steel probes). Consists of flush tank, rinse bath and ultrasonic bath.	3 stage cleaning bath (for cleaning stainless steel probes). Consists of flush tank, rinse bath and ultrasonic bath.
Weighing Module		Includes gripper arm & tube adapter, Readability range 0.0001 (g)
Temperature Module		Passive (dry ice) batch cooling module. Active (glycol) cooling module for recirculation of chilled air (<> 4°C).
Bulk Lid Dispenser		5000 µL capacity, accuracy to +/- 1% at full stroke. Capable of dispensing up to 6 separate fluids/reagents.
Bar Code Scanner		2D for reading pre-applied bar code labels.
Pipette Module		4 independent channels, 1000µL tips, liquid level and clog detection, accurate to +/- 2%
Power Rating	Up to 4 x 40 W brushless motors***	8 each 40 W brushless motors
Speed Control	Variable to 28,000 rpm	Variable to 28,000 rpm
Dimensions	37.5 in.(w) x 16 in.(d) x 27 in.(h) 96.5 cm.(w) x 40.6 cm.(d) x 68.6 cm.(h)	40 in.(h) x 28 in.(w) x 20 in.(d) 101 cm(h) x 71.1 cm(w) 50.8 cm(d)
Weight	95 lbs. (43 kg) (base unit)	150 lbs. (68 kg) (base unit)
Sound Level	< 75 db	< 75 db
Electrical Requirements	110VAC or 230VAC (Universal power input)	110VAC or 230VAC (Universal power input)
Environmental Requirements	Operates at ambient room temperature (50-95°F or 15-35°C). Base unit fits into most fume hoods. Custom enclosures available.	Operates at ambient room temperature (50-95°F or 15-35°C). Base unit fits into most fume hoods. Custom enclosures available.
Warranty	1 year	1 year

* Larger samples possible with the Prep 96 with 100 w motors.

** Other tubes may be adaptable, contact OMNI for details.

*** Larger motors available on the Prep 96 as custom.